

SLIDEBACK CARRIERS
AATAC
 HYDRAULIC WRECKERS

1002
 10-TON TOWING & RECOVERY UNIT



Optional Aluminum Body Shown

AATAC STANDARD DUTY

Standard Equipment

- Dual Variable Speed Hydraulic Winches
- Power Boom Elevation
- Power Boom Extension
- Dual Illuminated Control Panels
- Tailboard Chain Slots
- Aerodynamic Light Pylon
- Rear D-rings
- 26 Cubic Ft. Tunnel Box
- Galvanized Inner Fenders
- Patented Dual-Trac Lift System
- Power Up & Down Underreach
- Power In & Out Underreach
- Lift Arms & Receivers
- Safety Straps and Rachets
- Mud Flaps
- Bolt on Boom End
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

SPECIFICATIONS

Recovery Unit

Boom Ratings:	Retracted.....	20,000 lbs
	Extended.....	7,000 lbs
Maximum Boom Elevation:	Retracted.....	11'6"
	Extended.....	16'2"
Winches.....	10,000 lbs Each	
	First Layer	
Cable.....	3/8" x 100'	

Standard Duty Underlift

Retracted:	with Forks.....	6,500 lbs
	with Lift Arms.....	4,500 lbs
Extended:	with Forks.....	5,000 lbs
	with Lift Arms.....	4,500 lbs

Chassis recommended 14,000 to 20,000 GVW, 84" or 108" CA
 Ratings are based on structural factors only, not vehicle capability.
 Product specifications are subject to change without notice

Options

- Tow Sling
- Scotch Blocks
- Snatch Block
- Chrome Decor Group
- Push Bumper
- Bolt-on-Boom Jib
- Extra Tool Boxes
- Fiberglass Fender Flares
- Light Bar
- Deluxe Switch Panel
- Work Lights
- Hook Up Lights
- Tool Box Lights
- Pintle Hitch with Ball
- Remote Control System
- Power Dual Tilt System
- Frame Forks, Risers and Adapters