



2502

25-TON TOWING & RECOVERY UNIT



AATAC HEAVY DUTY

Standard Equipment

- Power Up & Down Underreach
- Power In & Out Underreach
- Full Hydraulic Wrecker Boom
- Twin Hydraulic Winches
- 96" Wide w/ Seamless Sides
- Aerodynamic Light Pylon
- Dual Variable Illuminated Controls
- Reinforced Tailboard
- Sealed Wiring Harness
- 2-14 Cubic Ft. Tool Boxes with Stainless Steel Latches
- Dual Track Underlift
- Rear Jacks w/ Removable Pads
- Lo-Pro Fork Receivers
- Frame Forks, Risers and Adapters
- Spring Lift Brackets
- Mud Flaps
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

SPECIFICATIONS

Recovery Unit

Boom Ratings: Retracted.....50,000 lbs
 Extended.....12,000 lbs

Maximum Boom Elevation:
 Retracted.....14'10"
 Extended.....19'

Winches.....25,000 lbs Each
 First Layer

Cable.....9/16" x 200'

Underlift

Retracted w/ Forks.....25,000 lbs
 Extended w/ Forks.....12,000 lbs

Chassis recommended 27,500 to 33,000 GVW, 120" - 180" CA
 Ratings are based on structural factors only, not vehicle capability.
 Product specifications are subject to change without notice.

Options

- Air Shift PTO
- Air Shift Winch Free-Spool
- Electric Controls 1-6 Functions
- Remote Electric Controls
- Tool Box Lights
- Snatch Block
- Scotch Blocks
- 24", 30", 32", and 36" Tunnel Tool Boxes
- Heavy Duty Tow Bar
- Heavy Duty Tirelift
- Center Spade
- Chrome Decor Group
- Aluminum Decor Group
- 25,000 lb Dragline Winch
- Fold Up Under Reach