



4502

45-TON TOWING & RECOVERY UNIT



AATAC HEAVY DUTY

Standard Equipment

- 180" CT Body
- 96" Wide w/ Seamless Sides
- 12" Full Length Frame
- Full Hydraulic Wrecker Boom
- Full Hydraulic Underlift
- Dual Hydraulic Winches
- Dual Hydraulic Pumps
- Aerodynamic Light Pylon
- Galvanized Inner Fenders
- Radio Remote Control
- Dual Variable Illuminated Controls
- Reinforced Tailboard
- Chain Slots for Scotch Blocks
- Sealed Wiring Harness
- Two Tunnel Tool Boxes w/ Stainless Steel Latches
- Patented Dual-Track Underlift
- Hydraulic Power Tilt Underlift
- Rear Jacks w/Removable Pads
- Mud Flaps
- Spring Cable Tensioners
- Air Winch Pools
- Illuminated Tool Box Compartments
- Chain Racks & Tool Holders
- Lo-Pro Fork Receivers
- Frame Forks, Risers and Adapters
- Spring Lift Brackets
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

SPECIFICATIONS

Recovery Unit

Boom Ratings:	Retracted.....	90,000 lbs
	Extended.....	28,000 lbs
Maximum Boom Elevation:	Retracted.....	19' 8"
	Extended.....	25' 5"
Winches.....	(2) 45,000 lbs Each	
	First Layer	
Cable.....	3/4" x 20'	

Heavy Duty Underlift

Retracted w/Forks.....	36,000 lbs
Extended w/ Forks.....	16,000 lbs
Extension Past Tailload.....	120'

Chassis recommended tandem axle 55,000 minimum GVW, 180" CT Ratings are based on structural factors only, not vehicle capability. Product specifications are subject to change without notice.

Options

- Air Shift PTO
- Air Cable Tensioners
- Heavy Duty Rear D-Rings
- Air and Electrical Hookups
- Light Bar Packages & Switch Panels
- Work Light Sets
- Wide Load Tow Light Bar
- Aluminum Decor Group
- Convenience Group
- Heavy Duty Truck Tire Lift
- Heavy Duty Truck Tow Bar
- Pintle Hook Attachments
- Fifth Wheel Plate
- Snatch Block (8" Sheave)