



AEC
EQUIPMENT CARRIER



AATAC INDUSTRIAL CARRIER

Standard Equipment

- 17' - 19' steel body with apitong floor
- Dual rear tilt cylinders
- Extension cylinder with wear rings
- Full height tubular cab protector
- Stake pocket body
- Dual illuminated control panels
- Positive lockdown system
- 36" x 14" x 16" Tool box with key
- Front chain trays
- Chassis reinforcing subframe
- 3/4 length lift frame
- 10,000 lb hydraulic winch
- 50' cable
- 2 front and 4 rear tie-downs
- Mud flaps
- Full length nylatron side pads
- Factory pre-assembled and tested
- Federal standard 108 lighting

SPECIFICATIONS

Load capacity.....	10,000 lbs
Platform size.....	17' - 19' x 8'
Floor.....	.5/4" apitong
Crossmembers.....	3" 58,000 PSI structural channel 12" OC
Side cylinder.....	3" diameter 108" stroke
1 1/2" chrome shaft, double-acting
Tilt cylinders (2).....	3" diameter, 16" stroke
1 1/2" chrome shaft, double-acting
Pump.....	Direct mount
Winch.....	Hydraulic 10,000 lbs
Cable.....	50' 3/8x6x37

Chassis recommended 14,250 to 24,000 GVW
 Available steel body with solid sides or removable rails.
 Ratings are based on structural factors only, not vehicle capability. Product specifications are subject to change without notice.

Options

- Tensioning roller guide
- Remote winch free spool
- Winch guard
- Pintle hitch mounting plate with safety hooks
- Pintle hitch with 2" ball
- Seamless tread plate floor