



A H D
HEAVY DUTY STEEL CARRIER



AATAC HEAVY DUTY CARRIER

Standard Equipment

- 20' - 28' steel body
- Dual front lift cylinders
- Extension cylinder with wear rings
- Tubular cab protector
- Stake pocket sides
- Positive lockdown system
- Tow light socket
- Dual illuminated control panels
- 48" x 18" x 18" Tool box w/ key
- Chassis reinforcing subframe
- 3/4 length lift frame
- Variable speed hydraulic winch
- 50' cable
- 96" wide body
- Four rear tie down slots
- Mud flaps
- Full length nylatron side pads
- PTO/pump combination
- Factory pre-assembled and tested
- Complete installation hardware
- Sealed Wiring Connectors

Options

- Cable tensioner
- Remote winch free spool
- Extra tool boxes
- Stainless tool box covers
- Removable side rails
- Trailer hitch
- Independent wheel lift
- Various cab protectors
- Snatch block
- Light bar
- Deluxe switch panel
- V-chains and straps
- Work lights
- Hook up lights
- Side D-rings
- Tool box lights
- Pintle hitch

SPECIFICATIONS

Load capacity.....	25,000 lbs
Platform size.....	20' - 28'
Floor.....	3/16" Solid smooth plate
Crossmembers....	3" 58,000 PSI structural channel 12" OC
Winch.....	Hydraulic 10,000 lbs
Cable.....	50' 3/8x6x37

Chassis recommended 18,000 to 33,000 GVW
 Ratings are based on structural factors only, not vehicle capability.
 Product specifications are subject to change without notice.
 Available removable rails.