



ASB
SLIDE BACK CARRIER



AATAAC MEDIUM DUTY CARRIER

Standard Equipment

- 17' - 19' Steel or 17' Aluminum Body
- 96" Wide Body
- Dual Front Lift Cylinders
- Extension Cylinder w/ Wear Rings
- Tubular Cab Protector
- Dual Illuminated Control Panels
- 6" Solid Sides
- Positive Lock Down System
- 12 Tie Down Plates (6 - Aluminum)
- Chassis Reinforcing Subframe
- 3/4 Length Lift Frame
- Full Length Nylatron Side Pads
- Reverse Hose Track System
- Variable Speed Hydraulic Winch
- 50' Cable
- Mud Flaps
- 36" x 14" x 16" Tool Box w/ key
- Tow Light Socket
- Safety Straps and Ratchets
- Sealed Wiring Connectors
- Factory Pre-assembled and Tested
- Complete Installation Hardware

Options

- Cable Tensioner
- Remote Winch Free-spool
- Extra Tool Boxes
- Aluminum Tool Box Door Covers
- Light Bar
- Deluxe Switch Panel
- Front Work Lights
- Hook Up Lights
- Tool Box Lights
- Side D-rings
- Removable Side Rails (Steel Only)
- 102" Wide Body (Steel Only)
- Tread Plate Floor (Steel Only)
- Trailer Hitch
- Pintle Hitch
- Various Cab Protector Styles
- Snatch Block
- V-Chains and Straps

SPECIFICATIONS

Load capacity:	Steel.....10,000 lbs
	Aluminum.....10,000 lbs
Platform size:	Steel.....17' - 19'
	Aluminum.....17' 4" - 18' 8" x 8"
Floor:	Steel.....3/16" Solid Smooth Plate
	Aluminum.....6061-T6 Air Craft Grade
Cross members.....	3" 58,000 PSI Structural Channel
Cable.....	50' 3/8" 6 x 37
Towbar capacity.....	3,500 Extended
Wheel Lift capacity.....	3,500 Extended
Winch.....	10,000 lbs, First Layer

Chassis recommended 12,000 to 24,000 GVW
 Ratings are based on structural factors only, not vehicle capability.
 Product specifications are subject to change without notice.