



SDS
SUPER DUTY SINGLE AXLE



AATAC INDUSTRIAL CARRIER

Standard Equipment

- 22' - 30' Steel Frame Body w/ Apitong Floor
- Two Tilt Cylinders - Rear
- One Slide Back Cylinder
- Full Height Cab Protector w/ Solid Bottom, Mesh Top, and Chain Rack
- 48" x 18" x 18" Tool Box w/ Key
- Stake Pockets 3 1/8" x 1 5/8"
- Chassis Subframe
- Hydraulic Dock Stabilizer
- Dual Illuminated Controls
- 2 Front and 4 Rear Tie-down Plates
- Mud Flaps
- Rear-Mounted Dual Control Panels
- One Year Warranty
- Complete Installation Hardware
- Pre-Assembled and Factory Tested
- Federal Standard 108 Lighting

SPECIFICATIONS

Load capacity.....	35,000 lbs
Platform size.....	22' - 28'
Floor.....	Wood, 1 3/8" Apitong
Crossmembers...3"	58,000 PSI Structural Channel 12" OC
Longitudinal members.....	6" H-beam 58,000 PSI Tensil
Slide Cylinder (1).....	4" Diameter 2" Chrome Shaft Double-Acting
Tilt Cylinders (2).....	4" Diameter 2" Chrome Shaft Double-Acting
Winch.....	15,000 lbs
Cable.....	9/16" x 65'

Options

- 1/8" Tread Plate Overlay
- Cable Tensioner
- 6" OC Crossmembers
- 3" Rub Rails
- Removable Side Rails
- Front Lift Cylinders
- Snatch Block
- Extra Tool Box
- Air Shift PTO
- D-Rings
- Pintle Hitch
- Remote Winch Control

Chassis recommended: SDS 27,500 - 33,000 GVW
 Ratings are based on structural factors only, not vehicle capability.
 Product specifications are subject to change without notice..